

Marking

CAS-Number	7440-59-7
Characterization acc. ADR	UN 1046, Helium, compressed, 2.2 Class 2, 1A

Cylinder Marking

shoulder:
brown

Essential properties

Colourless, odorless rare gas, compressed, very much lighter than air

Symbols of Risks

gas, compressed

Physical Properties

molecular weight:	4,0026 kg/kmol
gas density at 0°C and 1,013 bar:	0,1785 kg/m ³
density ratio to air:	0,1380

For additional safety information see Material-/safety data sheet No. *-HE-061A

Valves / Manifolds

Valve connection 200 bar: acc. to national standards
300 bar: ISO 5145 Nr. 1: W 30 x 2

Recommended Manifolds Spectrolab FM 51 / FM 52exact
Spectrochem FE 51 / FE 52exact

**Specifications / Cylinders**

		4.6	5.0	5.6 *	ECD	6.0	
Composition							
He	>	99,996	99,999	99,9996	99,9996	99,9999	Vol.-%
Impurities							
H ₂ O	<	5	3	2	2	0,5	ppmv
O ₂	<	5	1	1	1	0,5	ppmv
N ₂	<	20	4	1	1	0,5	ppmv
THC (as CH ₄)	<	1	0,2	0,1	0,1	0,1	ppmv
CO + CO ₂	<	-	-	0,1	-	0,1	ppmv
hal. HC	<	-	-	-	1	-	ppbv
Cylinders / Contents							
F 05 200 bar *		0,9	-	-	-	-	m ³
F 10 200 bar		1,8	1,8	-	-	1,8	m ³
F 20 200 bar *		3,7	-	-	-	-	m ³
F 50 200 bar		9,2	9,2	9,2	9,2	9,2	m ³
F 50 300 bar		13,2	13,2	-	-	-	m ³
B 12 * F 50 200 bar		110,4	110,4	-	-	-	m ³
B 12 * F 50 300 bar		158,1	158,1	-	-	-	m ³

Remarks

Applications:
Carrier gas for gas chromatography,
cooling gas for production of optical fibers,
leak detection,
filling gas for air bags,
component for diving mixtures,
shielding gas,
laser welding,
metallurgy,
meteorology (weather balloons),
reactor cooling gas,
aeronautics,
laser technology.

*: not available in each country



Messer Group GmbH
Gahlingspfad 31
47803 Krefeld
info@messergroup.com
www.messergroup.com